



# Product Information Platilon® H

## Thermoplastic Adhesive Films

### Typical Properties

Basic Material			Co-Polyamide	Polyurethane (Ester)	Co-Polyester
Grade			H 2	HU 2	H 5
Properties	Standards/Procedures	Units			
Density	calculated	g/cm <sup>3</sup>	1,10 <sup>1)</sup>	1,16 <sup>1)</sup>	1,27 <sup>1)</sup>
Softening range	TMA Onset	°C	≥ 100	≥ 75	≥ 120
	Kofler bench Knife	°C	110-120	90-105	105-120
Temperature stability	empirical	°C	≤ 110	≤ 60 <sup>2)</sup>	≤ 90
Appearance	visual	-	transparent	translucent	translucent
Resistance to plasticizer	empirical	-	very good	good	good
Barrier to plasticizer	empirical	-	yes	no	no
Laundry stability	empirical	°C	≤ 60	≤ 40	≤ 80
Chemical dry cleaning	empirical	-	good	limited	good
HF-weldability	empirical	-	very good	very good	good
Proposed glue line temperature	empirical	°C	130	110	140

These data are provided as general information only. They are approximate values and not intended for use in preparing specifications! Please contact us before writing specifications on this product.

- 1) calculated based on information by raw material suppliers and the film's composition
- 2) For short term temperature load on flat surfaces: 100 – 120°C

### Film Formats

Grade	Max. Width (mm)	Weight per area (g/m <sup>2</sup> )	Colour	Carrier/Release film (PE)
H 2	2100 <sup>3)</sup>	25 - 200	natural	yes <sup>4)</sup>
HU 2	2100 <sup>3)</sup>	25 - 200	natural	yes
H 5	2100 <sup>3)</sup>	25 - 110	natural	yes <sup>4)</sup>

- 3) Limitations depending on weight per area.
- 4) Carrier can be separated upon request at additional charge.

Our "General Conditions of Sale" also apply.

### Product Description

Platilon® H is the trade name for thermoplastic adhesive films made by Epurex Films. The range currently includes films based on:

- copolyamide
- thermoplastic polyurethane
- copolyester

### Properties

Platilon® H films combine excellent adhesion properties and easy processability with outstanding mechanical and chemical properties:

- good resistance to detergents
- high resistance to greases, oils and fuels

### Applications

The broad raw material range of Platilon® H allows excellent bonding to various substrates. Bonding applications include:

- automotive industry: for example interior parts and sound protection
- insulation industry
- wallpaper industry
- home textiles
- non wovens and foams

### Processing

The films may be heat activated by:

- infra-red systems
- flat-bed lamination
- heat and pressure calender
- ultrasonic, thermal impulse and HF-welding

### Advantages over other adhesive systems

- thermoplastic → no crosslinking, no pot life limitation
- economical processing
- exact thickness of adhesive layer
- free of plasticizers and solvents
- easy storage
- good environmental performance

The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products to determine suitability for your processing and intended uses. Your analysis must at least include testing to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Epurex Films GmbH & Co. KG, and Epurex Films GmbH & Co. KG has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. If the intended use of the product is for the manufacture of a pharmaceutical / medicinal product, medical device<sup>1)</sup> or of pre-cursor products for medical devices or for other specifically regulated applications which leads or may lead to a regulatory obligation of Epurex Films GmbH & Co. KG, Epurex Films GmbH & Co. KG must explicitly agree to such application before the sale.

Any samples provided by Epurex Films GmbH & Co. KG are for testing purposes only and not for commercial use.

Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request.

All information and including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed by you that you assume and hereby expressly release indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent.

1) Please see the "Guidance on Use of Covestro Products in a Medical Application" document. For more information on Covestro products in Medical Applications, please request from your sales support contact our Guidance document: GUIDANCE ON USE OF COVESTRO PRODUCTS IN A MEDICAL APPLICATION.

