



**Desmodur® white**


**Unfading support**  
New binder brings remarkable  
haptics and unfading color  
to polyurethane foam



## Infuse brightness

The future's bright for foam products and lingerie designs with color and light stable Desmodur® white from Covestro.

### QUV ultraviolet light accelerated aging test comparison



Desmodur® white is a new binder for polyurethane (PU) soft foam technology providing light fastness, remarkable haptics and high breathability that allows ultimate design freedom.

Traditional foam is made using aromatic PU raw material, which fades quickly under ultraviolet light exposure. Color-stable Desmodur® white is derived from aliphatic PU raw materials. Aliphatic PU was once reserved for high-grade cosmetic and medical base materials, owing to its lightness and stability. Now, with innovative foam technology a high-performing aliphatic PU foam solution is available and comes with remarkable performance characteristics.

Tests show that aliphatic PU foam offers unfading support, with non-discoloring performance, superior color fastness, haptics, air permeability, washability, and stretch resilience. Aliphatic PU foam offers foam products and high-end lingerie designers the material difference to infuse lasting brightness and color into their designs.

### Key technical features:

#### Color and light stability

Under sunlight exposure, traditional PU foam fades rapidly. High-intensity ultraviolet light accelerating tests on both aliphatic and traditional foam show superior light fastness after 312 hours of exposure. Additional tests reveal good resistance to heat and gas fumes.

#### Breathable comfort

Aliphatic PU foam has a high degree of breathability and comfort. Thanks to its ability to withstand demanding process conditions, aliphatic PU foam has the potential to increase breathability even further by using classical pore opening treatment.

#### Highly washable


Excellent shape and color retention, even after multiple wash cycles, makes aliphatic PU foam ideal for lingerie products.

#### Stretchable support

Stretch resilience provides support and comfort with good elongation stretch and support performance in both break tests and ball rebound tests.

#### Remarkable haptics

Aliphatic PU foam's more flexible molecular structure provides a remarkably soft and elastic feel, ideal for designing for comfort.



### Foam performance (exemplary):

Test standard ASTM D3574	Aliphatic polyurethane foam	After pore opening treatment
Density (kg/m <sup>3</sup> )	40	40
Hardness (Asker F)	12	20
Elongation (%)	142	178
Tensile strength (kpa)	92	112
Ball rebound (%)	62	65
Maximal air flow (l/min)	72	128 @44Pa



Color and light stability



Breathable comfort



Highly washable



Stretchable support



Remarkable haptics

### Notes

#### 1. QUV ultraviolet light accelerated ageing test is specified as follows:

Standard: GB/T 30669-2014

Light type: UVA-340 nm (similar to sunlight ultraviolet light spectrum)

Irradiance: 0.68 W/m

Conditions: continuously exposed to ultraviolet light at 60°C

#### 2. Compared with aromatic polyurethane foam sample:

Density 30 kg/m<sup>3</sup>, hardness 50 (Asker F)

The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products to determine suitability for your processing and intended uses. Your analysis must at least include testing to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Covestro, and Covestro has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. Any samples provided by Covestro are for testing purposes only and not for commercial use. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed by you that you assume and hereby expressly release indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent. Typical value: These values are typical values only. Unless explicitly agreed in written form, the do not constitute a binding material specification or warranted values. [PCS only: Values may be affected by the design of the mold/die, the processing conditions and coloring/pigmentation of the product. Unless specified to the contrary, the property values given have been established on standardized test specimens at room temperature.]



**Covestro Polymers (China) Co., Ltd.**  
Business Unit Coatings, Adhesives and Specialties  
No.33 Qiang Qiao Road,  
Shanghai, China 201206

[solutions.covestro.com/  
en/brands/desmodur](https://solutions.covestro.com/en/brands/desmodur)