

Platilon[®] Dureflex[®]

Multifunctional thermoplastic polyurethane (TPU) film – the material of choice.



Why Covestro TPU films?

The demand by consumers and producers of materials remains high. Independent of the application, high-quality standards and performance are not compromised.

This is where thermoplastic polyurethane (TPU) films show their strength. **Dureflex®** and **Platilon®** TPU films, manufactured by Covestro, represent a wide range of polymer compositions with excellent mechanical, chemical and thermal properties.

Thanks to the near unlimited potential to modify our products, Covestro can offer TPU monolayer, multilayer and co-extruded films customized to meet your specific needs and requirements. This benefits our customers in particular, with whom we work in close partnership to maximize their success.

We are also driving the development of our customized TPU films with sustainability in mind. Our efforts in this regard include waste reduction, the use of bio-based instead of fossil fuel raw materials, and pursuing a mass-balancing approach.



TPU properties

Thermoplastic polyurethanes are high-tech materials with a unique combination of versatile properties. TPU bridges the gap between hard thermoplastics and rubber. For instance, it can be deformed under tensile load, yet still returns to its original shape afterwards. Thanks to its molecular structure, TPU can be heated, melted and molded all over again.

The general properties of TPU are comprised of:

- Adhesion natural adhesion to a variety of substrates
- Abrasion resistance
- Barrier air and liquid barrier properties
- Elasticity high elasticity over the entire hardness range
- Flexibility over a wide temperature range
- Heat resistance
- High mechanical strength

- Printability
- Skin-contact medical grades
- Solvent- and plasticizer-free grades
- Tear and cut resistance
- Ethylene oxide (ETO)/Gamma sterilizable
- Suitable for heat lamination

Numerous forms of processing are possible: TPU films are highly suitable for thermal and flame lamination or for common welding processes. The material also offers excellent thermoforming properties.

Understanding the differences between types of TPU

TPUs generally can be separated into three types: aliphatics, aromatic polyesters and aromatic polyethers. Each offers a distinct set of qualities that recommend it for particular applications.

Aliphatics

- UV resistant
- Laminate to glass and polycarbonate sheet

Aromatic polyesters

- Effective barrier to gases
- Resistant to petrochemicals (e.g., gasoline, diesel fuel, aviation fuel, etc.)
- Resistant to many solvents, chemicals, fats, and greases

Aromatic polyethers

- Resistant to water, high humidity, and fungus
- Offer excellent hydrolytic stability
- Softer and more comfortable for skin contact
- Breathable impermeable to liquids but highly water vapor permeable





Comparison of TPU to other films

| Grade | Thermoplastic polyurethane | Flexible PVC | Co-polyester* | EVA (25% VA) | LDPE | HDPE |
|------------------------------------|----------------------------|--------------|---------------|--------------|--------------|-------------|
| Shore hardness | 70 - 95A | 60 - 95A | 30 - 80D | 85A | 55D | 50 - 76D |
| Specific gravity (Gms/cm3) | 1.14 - 1.35 | 1.30 - 1.50 | 1.07 - 1.28 | 0.95 | 0.915 - 0.94 | 0.94 - 0.97 |
| Ultimate tensile strength (PSI) | 4000 - 10000 | 2000 - 6000 | 2000 - 7500 | 4400 | 1300 - 2500 | 7000 - 7500 |
| Ultimate elongation (%) | 350 - 800 | 200 - 450 | 200 - 600 | 875 | 100 - 700 | 500 |
| Tear strength (PLI) | 300 - 700 | N/A | 100 - 300 | 350 | N/A | 330 |
| Puncture resistance | Excellent | Good | Good | Fair | Poor | Poor |
| Abrasion resistance | Excellent | Fair | Good | Fair | Good | Excellent |
| Oil resistance | Good | Fair/Good | Good | Good | Good | Good |
| Acid resistance | Good | Fair | Fair/Good | Good | Good | Good |
| Aqueous solution resistance | Good | Good | Good | Good | Good | Good |
| Ozone resistance | Excellent | Excellent | Excellent | Excellent | Good | Good |
| Water resistance | Good/Excellent** | Good | Good | Good | Excellent | Excellent |
| Low temperature flexibility | Excellent | Fair/Good | Fair | Good | Good | Good |
| Fabric lamination | Excellent | Fair/Good | Fair | Fair | Fair | Poor |
| Heat sealing | Υ | Υ | Υ | Υ | Υ | Υ |
| Solvent welding | Υ | Υ | Υ | Y | Ν | Ν |
| RF welding | Υ | Υ | Υ | Y | Ν | Ν |
| Thermoforming | Υ | Υ | Y | Y | Y | Y |

* Co-polyester data based on commercially available grade ** Polyester TPU - Good / Polyether TPU - Excellent



Multilayer films - a toolbox for your needs

Each individual TPU film brings its own customized properties; however, the combination in a multilayer film brings a higher level of performance. In this case, the total performance really is greater than the sum of its parts. Multiple features, like polymer carriers, surface finishes, colors and TPU chemistries can be brought together simultaneously to deliver a customized solution while still using a highly cost-effective manufacturing process.

Covestro's multilayer blown film capability allows different technologies and properties to be combined in a single processing step.

Multilayer toolbox options



Multilayer toolbox in practice

As part of a general drive to produce more sustainable and more wearable products, a customer was considering replacing solventbased TPU as a backing material for a wound dressing.

Critical requirements:

- A carrier with low release force for easy processing
- High breathable ether-TPU film for exudate management and long wear time
- Low friction, high matte effect surface for a premium appearance and feel
- Medically approved materials for the Class 2 device

Easy solution

By using Covestro multilayer technology, the customer was provided the product they needed:

Covestro was able to supply a 1mil (25 micron) TPU film with an MVTR of 4000g/m2/day, a medically approved color and a matte surface finish on the film.

The TPU film came with a carrier that had a release force adjusted to strip easily during processing. All of this was performed in a single process step which makes it possible to deliver a customized solution at an attractive price.





Wound dressing with TPU film and foam layers

A wide range of applications

With many different properties, the possible combinations of customized solutions are endless. TPU films are suitable for a wide range of consumer, industrial, medical, security, and mobility applications.



Automotive

- Seating
- Sun roof roll-up shades
- Steering wheel heater
- Sound insulation



Medical

- Smart patches
- Wound dressing
- Surgical drapes and packaging



Pipe relining

- Roof membranes
- Awnings
- Window shades



Textile / Sports & leisure

- Rain gear
- Tents
- Footwear
- Sleeping bags
- Emblems



Security & protection

- ID-cards
- Bullet-proof vests
- Bullet-resistant glazing

ur HH

Embedded electronics

- Wearables/Diagnostics
- Flexible circuits
- Embedded chips
- Heating and lighting elements

Want to learn more?

Covestro Specialty Films has a global technical and manufacturing footprint to support customers in Asia, Europe and the Americas. We are always ready to work with you in developing customized features that will provide an excellent combination of quality and performance.

Reach out to us or visit the Covestro Solution Center to find out more about our Specialty Films solutions (films.covestro.com) or send an email to films@covestro.com.







Covestro Deutschland AG Kaiser-Wilhelm-Allee 60

51373 Leverkusen Germany

coatings.covestro.com info@covestro.com films.covestro.com films@covestro.com The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, is beyond our control. Therefore, it is imperative that you test our products to determine suitability for your processing and intended uses. Your analysis must at least include testing to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Covestro, and Covestro has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. [EMEA only: If the intended use of the product is for the manufacture of a pharmaceutical/ medicinal product, medical device¹ or of pre-cursor products for medical devices or for other specifically regulated applications which lead or may lead to a regulatory obligation of Covestro, Covestro must explicitly agree to such application before the sale.] Any samples provided by Covestro are for testing purposes only and not for commercial use. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information, including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed by you that you assume and hereby expressly release and indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent. These values are typical values only. Unless explicitly agreed in written form, they do not constitute a binding material specification or warranted values.¹Please see the "Guidance on Use of Covestro Products in a Medical Application" document. Edition: 2022 · Printed in Germany