



Spotlights on high-performance adhesive applications

Spotlights on high-performance adhesive applications









Alternative raw materials



Topic

Circular solutions for our customers

Alternative raw materials for a circular economy

Lowering the ecological footprint by using biomass or waste streams

<complex-block><complex-block>

Available in larger volumes

Limited availability, but growing further

Relevant feedstocks and routes in early developed phase

covestro

High standards for introducing alternative raw materials covestro

Growing availability of alternative feedstocks for utilization in polymers

Covestro is transforming its activities toward a circular economy, responding to global sustainability challenges. One important pillar is the utilization of alternative feedstocks, which reduce the dependency on fossil resources and incorporate a lower carbon footprint.

According to our customer's needs, we offer alternative raw materials with distinctive performance profiles, based on bio-derived molecules or ISCC¹ PLUS certified drop-in solutions. This way, we promote the use of alternative feedstocks while maintaining the highest attribution standards.

4 ¹² C/ ¹⁴ C analysis	Measurement	Measurement of biogenic carbon
3 Trace-the-atom	Molecular attribution approach	Determination of sustainable share based on chemical reaction
2 Energetic determination	approach	or several outputs
1 Mass determination	Free attribution	Free attribution to one

¹ISCC = International Sustainability and Carbon Certification, internationally recognized system for sustainability certification of biomass and bioenergy



Covestro follows the trace-the-atom option for all products utilizing the mass balance approach

Covestro provides ¹²C/ ¹⁴C results for partly bio-based products in segregated production streams

Product offering promoting alternative feedstock utilization

Circular Intelligence with our CQ line

Supporting Customers



CQ-labeled materials cover at least 25 % alternative feedstock use



Reduced carbon footprint compared to fossil-based products confirmed via LCA¹



Chain-of-custody models can be segregated or mass-balanced



Product portfolio already comprises up to climate neutral² CQ products

¹LCA = Life Cycle Assessment ²Climate neutrality in terms of product carbon footprint (cradle-to-Covestro gate consideration) incl. biogenic uptake



Reducing dependency on fossil resources

covestro

Promoting alternative feedstock utilization for adhesive applications



Changing value chains require strong partnerships



We engage in joint solutions for a momentous circular transformation



Combining ultra-light construction with high performance, 2K PUbased adhesives from Sika are made with Covestro raw materials



Covestro enables H.B. Fuller to offer adhesives for the woodworking, composites, automotive, and textile sectors that reduce fossil resource use of their products



Engineered wood adhesives from Henkel, made with alternative raw materials from Covestro, are used in building and construction applications





Food-contact compliance



Full-spectrum PU solutions for flexible packaging

Focus Topic



Raw materials for foodcontact applications



Polyurethane (PU) adhesive polymers can be produced from a wide range of raw materials. The great adaptability of PU polymers allows adhesive manufacturers to provide tailor-made adhesive polymers for flexible packaging applications.

Our raw materials are manufactured in compliance with manufacturing best practices and fulfill the requirements of Regulation (EC) 1935/2004. Relevant compliance statements for suitable products can be requested for specific regions (e.g. Regulation (EU) No. 10/2011, FDA regulations in 21 CFR 175.105 (adhesives), Chinese hygienic standard GB 9685-2008).

Food-contact statements for suitable adhesive raw materials are available upon request

Covestro's main technologies for packaging applications



covestro





Productivity

Improving productivity for downstream users



Crosslinkers for water-borne 1K latent reactive adhesives

Polyurethane (PU) systems represent a benchmark in productivity and process efficiency in many industries. We strive to improve this efficiency even further by developing new, game-changing solutions. This is why we offer solutions that enable our valuechain partners to use materials more efficiently and reduce waste, such as raw materials for latent reactive systems.

\bigcirc

Significantly longer storage time of formulations (potlife) compared to 2K wb PU adhesives



Dried films/pre-coatings of latent reactive adhesives can be stored for months (open time)

No mixing of liquid adhesive by the user, resulting in clean, reliable, and efficient processes





Fast crosslinking for fast processing



High-performance 1K water-borne adhesives

<u>Desmodur[®] 2802</u> is a water-borne dispersion of a hydrophically-modified polyfunctional carbodiimide. It can be used as a crosslinker for water-borne adhesive formulations in roll-to-roll applications, with the following benefits:



High initial bond strength at room temperature for rapid further processing



One-component processing prevents mixing failures and adhesive waste



Impro



Improves chemical & thermal resistance of adhesive layer

Potlife up to 6 months (pH 7-9)



Easy processable powders

For non-yellowing hotmelt and solvent adhesive applications

Desmomelt[®] U is a new class of non-yellowing polyurethane (PU) adhesive raw material. Supplied as a coarse powder or pellet, it provides the bonding characteristics of well-known and proven solvent- or water-based heat activation PU adhesives in a 100% solid form.

Desmomelt[®] U can be processed as a hotmelt in various application forms, as well as dissolved to yield a solvent-based adhesive formulation.

Visit our Solution Center to find out more Desmomelt[®] U aliphatic polyurethane powders for adhesives



Product name	Molecular weight	Crystallization speed	Heat activation temperation [°C]	Viscosity [mPas [*]]
Desmomelt [®] U 410	Medium/low	++	50-60	20-50
Desmomelt [®] U 320	Medium	+	60-70	50-200
Desmomelt [®] U 230	High	o / +	70-80	200-600

*15 w% in methylethylketone (MEK) / water (16:1), (23°C, #62, 30 rpm)







Raw materials for high industrial hygiene standards



<u>Ultra line – keeping the quality up</u> and your business future-ready



Redefining industrial hygiene



Raw materials for high industry standards

Covestro is committed to continually improving products and setting new standards, especially in the field of industrial hygiene. Our new ultra line allows for further improvements through a consistent reduction of the specified residual monomer content, (kept below 0.1 percent), and helps users comply with legal regulations without additional administrative efforts.

	Conventional 2K PU	Covestro's ultra line
High-performance isocyanate technology	\checkmark	\checkmark
Improved industrial hygiene standard	\checkmark	$\checkmark\checkmark$
No additional efforts to comply with the proposed use restriction on diisocyanates*	×	\checkmark

*On August 24, 2020, the REACH Committee decided on the final draft of new occupational safety standards on the use of diisocyanates. The Commission Regulation entered into force on August 24, 2023

Water-borne industrial hygiene

Low-monomer crosslinker solutions for water-borne adhesives

Formulations utilizing polyurethane dispersions are well recognized for their very low odor and very low volatile organic compound emission levels. With our ultra line, industrial hygiene is increased even further, for 2K formulations as well.



Hydrophilized crosslinker with monomeric isocyanate content below 0.1%

Туре	Product
HDI	Bayhydur [®] ultra 304
HDI	Bayhydur [®] ultra 3100
IPDI	Bayhydur [®] ultra 401-70 MPA
IPDI	Bayhydur [®] ultra 401-70 MPA/X
HDI	Desmodur [®] ultra DA-L
HDI	Desmodur [®] ultra DN





Low-monomer solutions



For solvent-borne & solvent-free* adhesives

Crosslinker with monomeric isocyanate content below 0.1%

Туре	Product
HDI	Desmodur [®] ultra N 31100
HDI	Desmodur [®] ultra N 3300
HDI	Desmodur [®] ultra N 3500
HDI	Desmodur [®] ultra N 3600
HDI	Desmodur [®] ultra N 3700
HDI	Desmodur [®] ultra N 3800
HDI	Desmodur [®] ultra N 3900
PDI	Desmodur [®] CQ ultra N 7300

Туре	Product
TDI	Desmodur [®] ultra L 75
TDI/IPDI	Desmodur [®] ultra IL BA
TDI/IPDI	Desmodur [®] ultra IL EA
TDI/IPDI	Desmodur [®] ultra IL 1351 BA
TDI/HDI	Desmodur [®] ultra RN
IPDI	Desmodur [®] ultra Z 4470 BA
IPDI	Desmodur [®] ultra Z 4470 MPA/X
IPDI	Desmodur [®] ultra Z 4470 SN

Prepolymers with monomeric isocyanate content below 0.1%

Туре	Product
TDI	Desmodur [®] ultra E 15
HDI	Desmodur [®] ultra E 3370

Туре	Product
HDI	Desmodur [®] ultra E 30500
HDI	Desmodur [®] ultra E 30600

*In accordance to DIN EN 923





Innovative functionalities

Focus Topic

Functionalities for nextgeneration vehicles



Transluscent adhesives for new lighting designs



Electric vehicle components with safe, tough materials





Spotlights on high-performance adhesive applications | Europe

High-end requirements

Raw materials for challenging applications



Dispercoll[®] U 66: High bond for challenging lamination applications



Baymedix® | Medical polyurethanes









Disclaimer

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies for all cases where proprietary rights of third parties might be involved.

Our advice does not release you from the obligation to verify the information currently provided – especially that contained in our safety data and technical information sheets – and to test our products as to their suitability for the intended processes and uses.

The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility.

Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.