



Desmophen® Desmodur®

Increasing productivity and economic efficiency:  
Pasquick® polyaspartic technology in industrial  
applications



# Desmophen® NH, Desmodur® N Increasing productivity and economic efficiency: Pasquick® polyaspartic technology in industrial applications



### The challenge: increased productivity

Productivity is a very important factor in reducing process costs in the agricultural, construction and earthmoving equipment (ACE) and other industries. In close cooperation with our coating solutions' manufacturer, we can answer these industries' needs and improve their customers' paint processes.

### The solution: Pasquick® polyaspartic technology

Pasquick® is the brand name for our polyaspartic technology. Polyaspartics are a class of binders for high-quality, aliphatic 2K topcoats based on the Desmophen® NH and Desmodur® N product groups. Since they can be applied at high film thicknesses, a reduction in the number of layers is possible, making the coating process more economical. Depending on the substrate, even single-layer direct-to-metal (DTM) coatings can be considered.

Since Pasquick®-based coatings also cure quickly at room temperature, they are ideally suited to increasing the productivity of painting operations. And increased productivity helps to make the coating process more economical for the applicator. For example, energy costs are lower since the fast drying at room temperature means no stoving in a curing oven is required. Furthermore, the Pasquick® polyaspartic technology is suitable for the formulation of ultra-high solids.

### The most suitable Desmophen® NH aspartic products for industrial coatings

Product	Equivalent weight	Comment
Desmophen® NH 1420	278	Medium Reactivity
Desmophen® NH 1423	272	Medium Reactivity*
Desmophen® NH 1520	290	Low Reactivity

\* Better gloss retention than Desmophen® NH 1420.

The crosslinkers that best fit these products are Desmodur® ultra N 3600 and Desmodur® N 3900.

### Numerous practical examples of coating applications have proven the advantages of this technology over the past 15 years or more.



Covestro Deutschland AG  
Business Unit Coatings,  
Adhesives & Specialties  
51365 Leverkusen  
Germany

www.coatings.covestro.com  
cas-info@covestro.com

This information and our technical advice – whether verbal, in writing or by ways of trial – are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. The information is provided by Covestro without assumption of any liability. If any of the above mentioned regulations change after the date of declaration, this declaration is no longer valid. Covestro will strive to keep this information up-to-date. Our advice does not release you from the obligation to verify the information provided – especially that contained in our safety data and technical information sheets –, to check for updates of any information provided by us and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.  
Edition: 2019 · Order No.: COV00086505 · Printed in Germany · E