



HIGH-PERFORMANCE FILMS FOR MEDICAL APPLICATIONS

Modern wound management focuses on the patient's well-being, ensuring rapid wound healing and minimum pain, which are also aspects of key importance for health insurers and/or medical personnel. By reducing treatment times, wound management allows patients to be moved from in-patient to out-patient treatment, thus reducing nursing efforts and costs.

The plaster system allows excess moisture to escape and create an optimized wound climate that shortens the healing process and prevents additional stresses to the skin underneath the film. Moreover, the watertight film provides protection against external elements.

Platilon[®]



High-performance films for medical applications

Thermoplastic polyurethane (TPU) films are used in several different advanced wound management solutions. A variety of properties are customized to fulfill specific customers' requirements such as:


- Water vapor transmission to adjust dressing functionality
- Low friction
- Matte appearance to improve patients' comfort
- Type of carrier film

Platilon® film applications


- Wound dressings for OTC and advanced wound care
- NPWT dressings (Negative Pressure Wound Therapy)
- Surgical Incision films
- Fixations for wound covers and cannulae

Platilon® film properties


- Excellent breathability
- High elasticity & skin-friendliness
- Waterproof, viral & bacteria barrier
- Sterilization: gamma irradiation & Ethylene Oxide (EtO)
- Customizable surface – glossy, silk matte, extra matte



Customized colours



Release force adjustable



PE carrier as application & production aid

- Release force between TPU film and PE carrier adjustable
- PE carrier thickness from 35 to 70 µm available

Platilon® film types matrix

Platilon® types	Special characteristics	Features	Friction	Glossy	Silk matte	Extra matte	Thickness range [µm]	Available with stiff PP-carrier
4200-T	High tear resistance	<ul style="list-style-type: none"> • Low MVTR* • Low swelling in water contact • High mechanical stability 	o	x			15–100	x
9142-T			+		x		20–100	x
9158-T			++			x	20–100	x
4200 Z-T	High MVTR, No swell visible	<ul style="list-style-type: none"> • High MVTR* • Low swelling in water contact • High mechanical stability 	-	x			20–100	x
9101-T			+		x		20–100	x
9153-T			++			x	20–100	x
2202 C-T	Excellent MVTR, Switch effect in water contact	<ul style="list-style-type: none"> • Excellent MVTR* • High Swelling in water contact • Low mechanical stability 	--	x			15–100	x
9121-T			+		x		20–100	x
9147-T			++			x	20–100	x

* MVTR = Moisture Vapor Transmission Rate

® = Registered trademark of Epurex Films GmbH & Co. KG

+ = Low friction

o = Neutral friction

-- = High friction

The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products to determine suitability for your processing and intended uses. Your analysis must at least include testing to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Covestro, and Covestro has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. If the intended use of the product is for the manufacture of a pharmaceutical / medicinal product, medical device¹ or of pre-cursor products for medical devices or for other specifically regulated applications which leads or may lead to a regulatory obligation of Covestro, Covestro must explicitly agree to such application before the sale. Any samples provided by Covestro are for testing purposes only and not for commercial use. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed by you that you assume and hereby expressly release indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent. For more information on Covestro products in Medical Applications, please request from your sales support contact our Guidance document: GUIDANCE ON USE OF COVESTRO PRODUCTS IN A MEDICAL APPLICATION. These values are typical values only. Unless explicitly agreed in written form, they do not constitute a binding material specification or warranted values. The biocompatibility testing referenced above cannot assure the biocompatibility of final or intermediate products made from Covestro products or the suitability of such products for their use in a medical application, i.e., the test data cannot be used to conclude that any medical devices manufactured from the Covestro products meet the necessary requirements of ISO Standard 10993-1. It is the sole responsibility of the manufacturer of the final end-use product to conduct all necessary tests (including biocompatibility tests) and inspections and to evaluate the final product under actual end-use requirements.¹ Please see the „Guidance on Use of Covestro Products in a Medical Application“ document Edition: 2020 - Printed in Germany - E



Covestro Deutschland AG
 Specialty Films
 EMEA/LATAM
 41538 Dormagen,
 Germany
 films.covestro.com
 films@covestro.com