Changing the coatings game: **Pasquick**[®] for high-productivity applications.



Desmophen® Desmodur®

Changing the coatings game: **Pasquick**[®] for high-productivity applications





The challenge: Higher productivity

Protective coating manufacturers are often challenged when it comes to increasing the productivity of painting operations. This is especially true for the fast-growing market of direct-to-metal (DTM) coatings.

The solution: Pasquick®

Pasquick® is our polyaspartic technology brand. Pasquick® technology is a class of binders for high-quality, aliphatic 2K topcoats based on the **Desmophen® NH** and **Desmodur® N** product groups. They can be applied at high film thicknesses, so that the number of layers can be reduced. Since **Pasquick®** binders also cure quickly at room temperature, they are well-suited to boosting productivity in painting operations. The higher the productivity, the more economical the coating process becomes.

Another advantage of **Pasquick**[®] binders is their suitability for formulating ultra-high solids. Numerous practical examples of protective coating applications, for example, for wind turbine towers, have proven the advantages of this technology over the past 15 years. By using our high-productivity **Pasquick**[®] technology you can change the coatings game – to your advantage!

Most suitable Desmophen® NH aspartic products for protective coatings

Polyisocyanate	Solid content [%]	Equivalent weight	Viscosity [mPa · s]	Reactivity
Desmophen® NH 1420	100	276	Approx. 1,450	Medium
Desmophen® NH 1423 LF	100	274	Approx. 1,500	Medium*
Desmophen® NH 1520	100	290	Approx. 1,400	Low
Desmophen® NH 1523 LF	100	280	Approx. 2,000	Low*

Most suitable Desmodur® N polyisocyanates for protective coatings

* Improved industrial hygiene

Polyisocyanate	Solid content [%]	NCO content [%]	Viscosity [mPa · s]	Properties
Desmodur® ultra N 3600	100	23.0	1,200	For ultra-high solids
Desmodur® ultra N 3390	90	19.6	550	For high solids
Desmodur® NZ 486 BA	86	10.2	2,100	For prolonged pot life



Covestro Deutschland AG Kaiser-Wilhelm-Allee 60 51373 Leverkusen Germany

coatings.covestro.com info@covestro.com

The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, is beyond our control. Therefore, it is imperative that you test our products to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Covestro, and Covestro has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. If the intended use of the product is for the manufacture of a pharmaceutical/medicinal product, medical device¹ or for pre-cursor products for medical devices or for other specifically regulated applications which lead or may lead to a regulatory obligation of Covestro, Covestro must explicitly agree to such application before the sale. Any samples provided by Covestro, are for testing purposes only and not for commercial use. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information, including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understoad and agreed by you that you assume and hereby expressly release and indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in fact granted under the claims of any patent. These values are typical values only. Unless explicitly agreed in written form, they do not constitute a binding material specification or warranted values. 1) Please see the "Guidance on Use of Covestro Products in a Medical Application"