



Advanced polymer
technologies for can and coil.





Building a circular future, together.

The demand for more circular solutions is rising at a faster pace than ever before as the world collectively strives to tackle today's global challenges. Climate change, population growth, urbanization, digitalization and mobility are pushing players from every sector to find more sustainable solutions and to lay the foundations for climate neutrality by driving a Circular Economy. The challenge is not only to create these circular solutions, but also to maintain quality, durability and productivity.

Innovation is key to satisfying these demands and creating added value for customers, society and the environment by turning targets into realities. At Covestro, our long-standing expertise in aliphatic and aromatic polyisocyanates and more sustainable resins goes hand-in-hand with our purpose to constantly push boundaries in the search for future-oriented solutions. Through joint solutions, alternative raw materials, innovative recycling, and harnessing renewable energy, we're enabling coatings and adhesives producers to meet the circular challenge, here and now.

We're expanding our portfolio to include bio-based or recycled raw materials in coatings, adhesives, and specialty areas from cosmetics to textiles and 3D printing. Thanks to our mass balancing approach, we're helping close the loop by gradually replacing fossil fuels with ISCC-certified renewable resources. Our drop-in solutions ensure the high quality, consistent performance and easy processing that keep your production running smoothly. And we're constantly working to provide the global support, facilities and supply chain security you need to forge yet more circular innovations in infrastructure, automotive, furniture and more.

Material solutions can help turn circular targets into realities. Let's make the world a brighter place, together.



Can and coil.

Based on our strong collaborative partnerships with customers and our unique understanding of materials science and applications, we provide creative solutions for metal coating markets worldwide. Inspired breakthroughs that meet our customers' challenges and improve people's lives – now and for many generations to come.


We have long expertise in materials science, applications and in the value chain for metal packaging (can) and pre-coated metal (coil). Our portfolio covers a diverse range of resins and crosslinkers, from solventborne to waterborne, for pre-coated metal applications like construction and facades, and for metal packaging, including interior (food) and exterior can applications. Our broad technology expertise spans polyesters, acrylics, alkyds, and urethane chemistries. Our customer partnerships allow us to efficiently develop new products and improve existing ones to meet your toughest requirements, and do this in a way that's more sustainable. For instance, improved sustainability with enhanced properties like improved durability for facade panels, preferably using more sustainable and renewable building blocks. Offering tailor-made BPA-NI solutions for interior food cans. Sustainability is our main driver, making our products future-proof and prepared for the challenges ahead of us.



Product Selection Guide
Can coating raw materials



Product Selection Guide
Coil coating raw materials



Can

Solventborne saturated polyester and alkyd resins	SUPPLY FORM	VISCOSITY (Pa.s) 23°C		T _g (°C)	ACID VALUE		DESCRIPTION	MAIN FEATURES	FLEXIBILITY		STERILIZATION		SIZING	CLEAR VARNISH	3-PIECE CANS & GENERAL LINE		TUBES		
	SOLID CONTENT %	MOLECULAR WEIGHT (Mn)	OH-VALUE (APPROX.)	HARDNESS	WET ON WET	WHITE BASE COAT			INTERIOR BPA-NI	MONOBLOC AEROSOLS	B&B CANS								
Uralac® AN625 S1-60	S1	60	3.7–5.2	3,000	0	86	5–10	Short oil alkyd resin based on saturated fatty acids for overprint varnish	OPV, yellowing resis. wet on wet	2	5	5	5		●●●	●●	●●●		
Uralac® AN637 S2-60 ND	S2 ND	60	2.5–4.0	4,500	16	17	2–10	Short oil alkyd resin based on versatic acids for overprint varnish	OPV flexibility	5	2	5	5		●●●		●●●		
Uralac® SN805 S2G3-65 ND	S2G3 ND	65	2.6–3.6	3,000	0	110	4–8	Saturated polyester resin for general purpose	High solids	2	3	5	1		●●	●●	●●●		
Uralac® SN808 S2G3-50 ND	S2G3 ND	50	2.0–2.8	5,200	28	40	2–5	Saturated polyester resin for white base coat	General Line	4	4	5	2		●●●		●●●		
Uralac® SN825 M1-50 ND	M1 ND	50	4.2–5.6	5,000	50	10	8–10	Saturated polyester resin for aerosols	Adhesion on aluminium	4	5	5	2		●●●	●●		●●●	
Uralac® SN833 S2-55 ND	S2 ND	55	3.6–4.6	6,000	32	22	3–5	Saturated polyester resin for flexible white base coat	Deep draw, flexibility	5	3	5	2		●●●		●●●	●●	
Uralac® SN842 S2-60 ND	S2 ND	60	12.5–16.5	4,000	25	25	5–10	Saturated polyester resin for general purpose	Flexibility, block resistance	5	3	5	3		●●●		●●●	●●	●●●
Uralac® SN852 S2F-60 ND	S2F ND	60	4.5–6.5	4,300	21	45	4–7	Saturated polyester resin for white base coat	Good compatibility BPA-NI	4	3	5	2		●●●	●●	●●●		
Uralac® SN856 S2G3-50 ND	S2G3 ND	50	1.4–2.0	4,000	58	55	0–5	Saturated polyester resin for interior BPA-NI	Hardness chemical BPA-NI	3	5	5	2		●●	●●	●●●	●●●	
Uralac® SN881 GG4-55	GG4	55	1.1–1.3	4,500	16	25	0–4	Saturated polyester resin for overprint varnish	OPV, flexibility, wet on wet	5	2	5	5		●●●		●●●	●●	
Uralac® SN885 S2G3-60 ND	S2G3 ND	60	5.5–8.5	5,000	29	20	1–4	Saturated polyester resin for white base coat	General Line	4	3	5	2		●●●	●	●●	●●●	●
Uralac® SN898 S2G3-55 ND	S2G3 ND	55	1.6–2.1	5,000	7	24	0–3	Saturated polyester resin for interior BPA-NI	Flexibilizer BPA-NI mix resin	5	2	4	2			●●●	●●●		
Uralac® SN908 S2E5-50 ND	S2E5 ND	50	1.8–2.6	5,000	51	24	3–8	Saturated polyester resin for aerosols	Good adhesion on aluminium	3	5	5	1	●	●●●		●	●●●	●
Uralac® SN908 S1E5-50	S1E5	50	1.8–2.6	5,000	51	24	3–8	Saturated polyester resin for aerosols (not intentionally added naphthalene)	Good adhesion on aluminium	3	5	5	1	●	●●●		●	●●●	●
Uralac® SH970 S2E5-40 ND	S2E5 ND	40	3.5–4.5	15,000	67	7	0–4	High molecular weight saturated polyester BPA-NI	Mix resin high Tg	5	5	5	1	●		●	●●	●●	
Uralac® SH973 S1E5-40	S1E5	40	3.8–4.7	20,000	65	7	8–10	High molecular weight saturated polyester BPA-NI	Reactive	5	5	5	1	●		●●●	●●		
Uralac® SH976 S1E5-40	S1E5	40	3.5–4.5	15,000	40	7	0–3	High molecular weight saturated polyester BPA-NI	Flexible BPA-NI compatibility	5	4	5	1	●●●	●●		●●●	●●●	●
Uralac® SH979 S1F-45	S1F	45	3.5–5.0	11,000	55	7	5–9	High molecular weight saturated polyester BPA-NI	Universal BPA-NI	5	5	5	1		●●		●●●	●●●	
Uralac® SH980 S1F-50	S1F	50	1.7–2.3	9,000	14	20	0–3	High molecular weight saturated polyester BPA-NI	Flexible BPA-NI	5	3	4	3		●		●●●	●●●	
Uralac® SH992 S1-45	S1	45	1.0–1.8	8,000	93	10	0–3	High molecular weight saturated polyester BPA-NI	Chemical resistance BPA-NI	5	5	5	1				●●●	●●●	
Uralac® SH993 S1-45	S1	45	2.4–3.3	10,000	93	4	0–3	High molecular weight saturated polyester BPA-NI	Chemical resistance BPA-NI	5	5	5	1				●●●	●●●	

Can

	SUPPLY FORM	VISCOSITY (Pa.s) 23°C		T _g (°C)	ACID VALUE		DESCRIPTION	MAIN FEATURES	FLEXIBILITY		STERILIZATION		SIZING	CLEAR VARNISH		3-PIECE CANS & GENERAL LINE		TUBES		
		SOLID CONTENT %	MOLECULAR WEIGHT (Mn)		OH-VALUE (APPROX.)				HARDNESS	WET ON WET	WHITE BASE COAT	INTERIOR BPA-NI	MONOBLOC AEROSOLS	B&B CANS						
Water dilutable (acrylated) saturated polyester resin																				
Uradil™ SZ250 M1-40	M1	40	2.0–9.0	3,000	31	40	50–55	Acrylic modified saturated polyester resin for B&B	Good retort, low co-solvent	4	5	5	3		•	•••				•••
Uradil™ SZ260 G3-65	G3	65	4.0–11.0	2,500	24	17	57–63	Acrylic modified saturated polyester resin for B&B	Good flow	4	5	3	3		•••	••				•••
Acrylic modified saturated polyesters																				
Uralac® SC890 S2G3-50 ND	S2G3 ND	50	0.8–1.0	3,500	33	35	45–50	Acrylic modified saturated polyester resin	Good flow	4	5	4	2		•••					•••
Epoxy esters																				
Uranox™ EE3 S2-50 ND	S2 ND	50	18–28	6,000	30		0–5	Epoxy ester resin for overprint varnish	OPV, Good yellowing resistance	3	4	5	5			•••		•••		
Uranox™ EE4 S2-50 ND	S2 ND	50	2.2–2.8	6,000	13		0–4	Epoxy ester resin for overprint varnish	OPV, flexibility	4	3	5	5			•••		•••		
Uranox™ EE7 S2G3-57 ND	S2G3 ND	57	2.6–4.1	5,400	18		0–4	Epoxy ester for high solids overprint varnish	OPV, higher solids EE3	3	3	5	5			•••		•••		
Specialties																				
Uradil™ DD80		73	6.9–10.1				45–55	Epoxy phosphate ester for water-based coatings	Adhesion promoter water-based	4	5	5			••	••			••	•••
Uralac® SN865 S2-75 ND	S2	75	6.0–7.0	4,500	–17	22	3–7	Saturated polyester resin to obtain a more flexible coating	Flexibilizer	5	1	3	2	•	•			•	•	
Crosslinkers																				
Desmodur® BL 3175	S1	75	2–4					HDI crosslinker blocked with MEKO	Flexible	5	5	5		•	•••	•••		•••	•	•
Desmodur® BL 2078/2	S1	60	1.7					IPDI crosslinker blocked with caprolactam	Food contact (FCN 695)	3	5	5		•	•••	••	•••	•••	••	•
Desmodur® BL 3272	F	72	2.7					HDI crosslinker blocked with caprolactam	High film thickness	5	5	5		••	•••	•••		•••	•	•
Baybond® XL 3674	W	30	< 1					Waterborne dispersion HDI crosslinker blocked with caprolactam	Water-based, flexible	5	5	5		••	•••	•••		•••	•	••

Coil

	SUPPLY FORM	VISCOSITY (Pa.s) 23°C		T _g (°C)	ACID VALUE		DESCRIPTION	MAIN FEATURES	SUBSTRATE	HARDNESS		TOPCOAT EXTERIOR	APPLIANCES		BACKING COAT		
		SOLID CONTENT %	MOLECULAR WEIGHT (Mn)		OH-VALUE (APPROX.)	STRUCTURE					FLEXIBILITY	WEATHERABILITY	TOPCOAT INTERIOR	PRIMER			
Solventborne resins																	
Uralac® SH970 S2E5-40 ND	S2E5 ND	40	3.5–4.5	15,000	67	7	0–4	L	High molecular weight saturated polyester for primer coating	Corrosion protection	Steel, HDG	5	5	2	•	•	•••
Uralac® SH973 S1E5-40	S1E5	40	3.8–4.7	20,000	65	7	8–10	SB	High molecular weight saturated polyester for primer coating	Corrosion protection	Steel, HDG	5	5	2	•	•	•••
Uralac® SN989 S1F-60	S2F ND	60	3.5–7.0	4,500	51	23	1–4	L	Standard molecular weight saturated polyester for primer coating	Superdurable	Steel, HDG	3	4	2	•	•	•••
Uralac® SN804 S2-65 ND	S2 ND	65	4.2–4.7	3,000	23	35	0–4	SB	Saturated polyester resin for topcoat superdurable	High solid	Steel, HDG, alu	3	4	5	•••	••	
Uralac® SN805 S2G3-65 ND	S2G3 ND	65	2.6–3.6	3,000	0	110	4–8	B	Saturated polyester resin for topcoat with high reactivity and for back coating	Superdurable	Steel, HDG, alu	2	4	4	••	•	•••
Uralac® SN806 S2G3-66 ND	S2G3 ND	66	1.8–3.0	3,200	14	37	0–1	SB	Saturated polyester resin for outdoor durable topcoat	Domestic appliance	Steel, HDG, alu	3	4	5	•••	••	
Uralac® SN830 S2-60 ND	S2 ND	60	4.0–4.7	4,500	26	28	3–6	L	Saturated polyester resin for topcoat domestic appliances	All round	HDG, alu	4	4	4	•••	•	•••
Uralac® SN831 S2G3-60 ND	S2G3 ND	60	2.7–3.6	5,000	25	32	2–5	SB	Saturated polyester resin for topcoat	Flexible	Steel, HDG, alu	4	4	4	•••	•	••
Uralac® SN833 S2-55 ND	S2 ND	55	3.6–4.6	6,000	32	22	3–5	L	Saturated polyester resin for flexible topcoat and domestic appliances	Flexible	HDG, alu	4	3	3	••	••	•••
Uralac® SN837 S2G3-65 ND	S2G3 ND	65	4.0–6.0	4,000	23	40	0–3	SB	Saturated polyester resin for flexible and high durable coatings	Flex, aging, cold flex	HDG, alu	4	3	4	•••	••	
Uralac® SN844 S2G3-60 ND	S2G3 ND	60	2.8–3.2	4,000	19	32	0–4	SB	Saturated polyester resin for topcoat	High yield, flex	Steel, HDG, alu	4	4	3	•••	•	•
Uralac® SN857 S1G3-70	S1G3	70	2.7–3.4	2,500	8	50	2–5	L	Saturated polyester resin for high yield topcoat	Flexibilizer	Steel, HDG, alu	4	2	3	••	••	
Uralac® SN865 S2-75 ND	S2	75	6.0–7.0	4,500	–17	22	3–7	L	Saturated polyester resin for blending to obtain a more flexible coating	Flexibilizer		5	1	3	•	•	•
Uralac® SN867 S2E5-60 ND	S2E5 ND	60	4.2–4.8	6,000	–10	15	0–3	L	Saturated polyester resin for blending to obtain a more flexible coating	Good adhesion alu		5	1	3	•	•	•
Uralac® SN885 S2G3-60 ND	S2G3 ND	60	5.5–8.5	5,000	29	20	1–4	L	Saturated polyester resin for flexible topcoat	Good adhesion alu	Alu	5	3	3	•••	••	•

Coil

	SUPPLY FORM	VISCOSITY (Pa.s) 23°C		T _g (°C)	ACID VALUE		DESCRIPTION	MAIN FEATURES	SUBSTRATE	HARDNESS		TOPCOAT EXTERIOR	APPLIANCES		BACKING COAT				
		SOLID CONTENT %	MOLECULAR WEIGHT (Mn)	OH-VALUE (APPROX.)	STRUCTURE	FLEXIBILITY				WEATHERABILITY	TOPCOAT INTERIOR	PRIMER							
Waterborne resins																			
Uradil™ SZ250 M1-40	M1	40	2.0–9.0	3,000	31	40	50–55	SB	Waterborne saturated polyesters for topcoat and primer applications	Corrosion protection		3	3	3	••	••		••	
Crosslinkers																			
Desmodur® BL 3175	S1	75	3.3						HDI crosslinker blocked with MEKO	Flexible		5	4	5	••	•••	••	•••	•••
Desmodur® BL 4265	S1	65	11						IPDI crosslinker blocked with MEKO	Hardness & chemical resistance		4	5	5	••	•••	••	•••	•••
Desmodur® PL 350	M1	75	4.3						HDI crosslinker blocked with DMP	Excellent thermal yellowing resistance		5	4	5	•••	•••	•••	••	•
Desmodur® eco BL 7175	M1	75	10						PDI crosslinker blocked with DMP	Partially bio-based, bio-content approx. 32%* in supply form		5	4	5	•••	•••	•••	••	•

*¹⁴C measurement according to ASTM-D6866 standard**Abbreviations**

B	branched resin
E5	dibasicester
F	methoxypropylacetate
G	propyleneglycol monomethylether
G3	butylglycol
G4	dipropylene glycol monomethylether
L	linear resin
M1	mixture of solvents
ND	naphthalene depleted
S1	solvent naphta 100
S2	solvent naphta 150 ND
S5	solvent naphta 200 ND
SB	slightly branched resin
W	water
HDI	hexamethylene diisocyanate
IPDI	isophorone diisocyanate
PDI	pentamethylene diisocyanate
MEKO	methylethylketoxime
DMP	dimethylpyrazol

• moderately recommended •• recommended ••• strongly recommended

Remark 1 = not good, 5= excellent



Covestro Deutschland AG
Kaiser-Wilhelm-Allee 60
51373 Leverkusen
Germany

covestro.com

The manner in which you use our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, is beyond our control. Therefore, it is imperative that you test our products to determine suitability for your processing and intended uses. Your analysis must at least include testing to determine suitability from a technical, health, safety, and environmental and regulatory standpoint. Such testing has not necessarily been done by Covestro, and Covestro has not obtained any approvals or licenses for a particular use or application of the product, unless explicitly stated otherwise. [EMEA only: If the intended use of the product is for the manufacture of a pharmaceutical/medicinal product, medical device¹ or of pre-cursor products for medical devices or for other specifically regulated applications which lead or may lead to a regulatory obligation of Covestro, Covestro must explicitly agree to such application before the sale.] Any samples provided by Covestro are for testing purposes only and not for commercial use. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information, including technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed by you that you assume and hereby expressly release and indemnify us and hold us harmless from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent. These values are typical values only. Unless explicitly agreed in written form, they do not constitute a binding material specification or warranted values.
¹ Please see the "Guidance on Use of Covestro Products in a Medical Application" document.

Edition: December 2021 · Printed in Germany